



COSMO® CL-300.220

*** COSMOPLAST 763

Tool cleaner

Examples for Application

- Cleaning of tools and adhesive applicators from reaction adhesives which have not cured

1-C-PUR Reaction adhesives

2-C-PUR reaction adhesives

1-C-STP Reaction adhesives

2-C-STP reaction adhesives

Special Properties

- Also dissolves partially cured/cured adhesives
- Very economical
- Intensive cleaning effect

Technical Data

Basis	Mixture of carbon acid derivates
Density as per EN 542 at +20 °C	approx. 1.10 g/cm ³
Processing temperatures	from +5 °C to +30 °C

Instructions for use

Acclimatise the product before the application.

Always check the surfaces to be cleaned for compatibility!

Due to the strong cleaning effect, test the lacquer, the plastic materials, the seals, the rubber rollers, etc, whether they are sufficiently resistant before starting the application.

In fresh/partially cured condition, the above mentioned reaction adhesives are cleaned away from the tools or bonding substrates using a paintbrush or a brush.

Due to the slow evaporation of the cleaner, we recommend re-cleaning of the material surfaces with COSMO® CL-300.150 depending on the further processing.

Tools which are wetted with 1-C reaction adhesives, can be put into a cleaning bath with COSMO® CL-300.340 until the next day to delay the further reaction of the adhesive system.

The cleaner should not be used for pre-cleaning of the bonding surfaces of the substrate!

Important instructions

Only instructed personnel in specialist firms are allowed to use the product!

Our user instructions, processing guidelines, product- and performance data, and other technical statements are only general directives; they describe only the condition of our products (values, determination of values on the date of completion) and the performances do not represent a warranty in the sense of § 443 BGB. **Because of the wide variety of applications of the individual product and the relevant special conditions (e. g. processing parameters, material characteristics, etc.), it is up to the user to test it itself;** our free expert advice for application provided in speech, writing, and as test is nonbinding.

Please, also consider the Safety Data Sheet!

Storage

Store the hermetically closed original trading units, in a dry place at temperatures of +15 °C to +25 °C no direct sun radiation.

While transported within the usual transport times, the product may be exposed to temperatures from -30 °C to +35 °C.

Storage life in unopened original packaging: 24 Months.

Packaging

10 l metal canister

Accessories

COSMO® SP-870.100 - Pulp cleaning cloth





COSMO® CL-300.220

*** COSMOPLAST 763

Tool cleaner

200 l metal bung hole drum

